

**SELF-PROPELLED COMPO CASTER**

**Takakita**

**自走コンポキャスター**



**SC-211SK・SC-211F**

**For soil preparation in small fields,  
greenhouses, and orchards!**

**Front spray**



**SC-211SK**



**Available for  
Right half or  
Left half**

**Simple mix of organic  
and chemical fertilizers**

**Side spray**



**SC-211F**

**Left and right or  
both sides switching**



## ■ Simple mixing of organic and chemical fertilizers is possible!

The agitator, which rotates at low speed, enables simple mixing. Large opening at the bottom of the hopper allows mixing of compound fertilizers including fishmeal and dry compost.

(SC-211SK)




Agitator

BEFORE



AFTER



Mixture of rice bran, rice husks, and compost

## ■ Easy spray volume adjustment

Shutter open/close lever allows adjustment of spray volume.

SC-211SK: 14 level

SC-211F : 7 level



## ■ Easy fertilizer loading

The hopper capacity is 200L. The hopper is as low as 1m above the ground for easy use.



## ■ Transmission & Steps



The transmission has 6 forward and 2 backward steps, starting from low speed (0.4 km/h) for easy loading onto trucks and crossing between rice paddies. The step stand is for easy riding and operation.

## ■ Attachment for SC-211SK

### Apron attach SC-E3

It can reduce the effect of wind on fertilizer spreading.

### Inclined spread attach SC-K3

It is effective for spraying toward inclines, such as in orchards.


## ■ One side or both sides spraying(SC211F)

It is possible to switch between spraying on one side or both sides. Pelleted or granular fertilizers can be spread up to 4 m per side.



## ■ Adjustable spray angle(SC-211F)

Spray distance can be adjusted by changing the angle of the spray opening from upward and downward from the ground.



### ■ Specifications

Model Name	Hopper (L)	Machine Size(mm) L×W×H	Weight (kg)	Engine Output (kW{PS})	Fuel	Effective spray width (m)	Working Speed	Working Efficiency (min./10a)	Available Fertilizer
SC-211SK	120	1,690~1,810× 1,040× 1,060~1,140	23.6	2.3 {3.1}	Gasoline	Chemical Fertilizer 6.0~10.0 Organic Compost 2.5~3.5	Forward 0.4~4.4 (6 Level) Backward 0.6~2.1 (2 Level)	Chemical 4~34 <sup>*1</sup> Organic 7~90 <sup>*1</sup>	Granular, pellet, sandy, powdery, and Organic fertilizer (45% or less moisture)
SC-211F			24.8			Pelleted / Granular Max. 4.0 on one side Mixed Fertilizer Max. 2.0 on one side		-	Granular, pellet, and sandy <sup>*2</sup>

\*1 These figures are for a trace amount of spraying at the lowest speed (0.4 km/h).

\*2 It is not available for organic fertilizers, rice bran, slaked lime, or other powdered fertilizers.

※主要諸元・写真は、改良のため予告なく変更することがあります。



### 安全作業

農業機械は取扱説明書をよく読み正しい操作を心がけましょう。  
農業機械の使用前後には点検・整備を心がけましょう。

二次元コードからも  
タカキタのホームページに  
アクセスできます。



製品のご相談は・・・

株式会社 **タカキタ**

本社工場／〒518-0441 三重県名張市夏見2828番地 TEL.0595(63)3111(代) FAX.0595(64)0857  
札幌工場／〒007-0882 札幌市東区北丘珠2条3丁目1番20号 TEL.011(781)1111(代) FAX.011(781)1113  
営業所／札幌・豊富・北見・中標津・帯広・東北・南東北・関東・関西・中国・九州・南九州  
URL: <https://www.takakita-net.co.jp>