

# MAIZE ROLL BALLER 細断型ローバレー・細断型コンビラップ

MR-821・1021R / MW1011H・MW1231

## High Quality Silage of Corn and TMR 細断型ローバレー



MR-821



MR-821

Bale Size Φ85・90×85cm



MR1021R

Bale Size Φ100×85cm

## High-Efficient System From Round Baling to Bale Wrapping 細断型コンビラップ



MW1231 + MW1231-CC



MW1011H

Bale Size Φ100×85cm



MW1231

Bale Size Φ115×100cm

Takakita

新製品  
NEWS

### ■ Specification

		Round Baler for Chopped Material	
Models		MR-821	MR1021R
Function		Round Baler	
Bale Size(cm)		φ 85/90 x 85	φ 100 x 85
Bale Weight(kg)		300~450	415~500
Remote Control		Standard Equipment	
Dimensions(mm)	Overall Length	5,110	6,000
	Overall Width	1,910	1,910
	Overall Height	2,600	2,340
Machine Weight(kg)		1,875	2,705
Hopper Capacity(m³)		2.5	3
Tire Size		11L - 15 6PT	11.5/80 - 15 8PR
Suitable Tractor(kW {HP})		22.1~73.6 {29.6~98.7}	25.7~73.6 {34.5~98.7}
Installation		Drawbar-towed	
Driving Method {Rational Speed(rpm)}		PTO Drive {540}	PTO Drive {400rpm}
Net Size		103cm or 123cm x 2,000m	
Baling Efficiency(pieces/h)		20	30

※Bale Weight depends on crop and moisture content.

### ■ Specification

		Chopping Combi Bale Wrapper	
Models		MW1011H	MW1231
Function		Round Baler + Bale Wrapper	
Bale Size(cm)		φ 100 x 85	φ 115 x 100
Bale Weight(kg)※		415~500	700~800
Remote Control		Standard Equipment	
Dimensions(mm)	Overall Length	When Operating: 9,520 When Moving: 8,900	When Operating: 10,340 When Moving: 9,650
	Overall Width	When Operating: 3,530 When Moving: 2,330	When Operating: 3,520 When Moving: 2,350
	Overall Height	When Operating: 2,790 When Moving: 2,790	When Operating: 2,800 When Moving: 3,220
Machine Weight(kg)		4,205	5,305
Hopper Capacity(m³)		3.0	4.0
Tire Size		11.5/80 - 15 8PT	16/70 - 20 12PR
Suitable Tractor(kW {HP})		25.7~73.6 {34.5~98.7}	59.1~95.6 {60~128.2}
Installation		Drawbar-towed	
Driving Method		PTO Drive {400}	
Net Size		103cm or 123cm x 2,000m	123cm x 2,000m
Film Size		50cm x 1,800m Use two films at the same time	
Baling Efficiency(pieces/h)		30	
Factory Option		Cleaning device attachment	

※Bale Weight depends on crop and moisture content.

※仕様・写真は、改良のため予告なく変更することがあります。

You can access our website from the QR code.



安全作業

農業機械は取り扱い説明書をよく読み正しい操作を心がけましょう。  
農業機械の使用前後には点検・整備を心がけましょう。



株式会社 **タカキタ**

本社工場／〒518-0441 三重県名張市夏見2828番地 TEL.0595(83)3111(代) FAX.0595(84)0857  
札幌工場／〒007-0882 札幌市東区北丘2条3丁目1番20号 TEL.011(781)1111(代) FAX.011(781)1113  
営業所／札幌・豊富・北見・中標津・帯広・東北・南東北・関東・関西・中国・九州・南九州  
URL: <http://www.takakita-net.co.jp>

製品のご相談は...



# Forage Revolution With Takakita Balers



One Operation



Accompanying Work



Stationary Operation



By compressing and packing dent corn shredded in a cutting length of about 10 mm with a corn harvester into a cylindrical shape and packing it, a high-density and high-quality roll bale are made. In addition, it can be managed in units of 1 bale, preventing deterioration loss during a rainy season and making it possible to feed high-quality corn silage for the whole season.

## Round Baler for Chopped Material (MR-821, MR1021R)

### Remote Controller



A remote controller is standard equipment.



MR-821



MR1021R

### Variable Diameter (MR-821)



Bale diameter can be selected as 85 cm or 90 cm depending on feeding volume.

### Conveyor Hopper



A conveyor at the bottom of the hopper smoothly feeds the crop to the chamber. The hopper capacity is: MR-821= 2.5m<sup>3</sup>, MR1021R= 3.0m<sup>3</sup>



A hatch is attached to the front of the hopper for easy maintenance.



Check windows on the front and side of the hopper allow the operator to check the amount of feed remaining inside the hopper. (MR-821)



MR-821



MR1021R

Spare Net Holder

### Gull Wing Cover (MR-821)

The covers on both sides of a gull-wing system open and close vertically for easy maintenance.




Automatic lubrication pump




### Net Installing

The netting device can be slid to the right and left sides of the machine for easy net maintenance. (MR-821)



## Year-round Feeding Of Corn Silage

Corn silage is ready for feeding in about one month. After that, it can be kept fresh for about a year until the wrap is opened, allowing year-round feeding of high-quality corn silage.



### Stable Lactic Acid Fermentation

Bales are quickly wrapped (6 or more layers) to increase airtightness, suppress butyric acid fermentation, and produce good quality, stable lactic acid fermentation.

### Silage Favored By Cows

Even in the summer, when cows' energy levels are low, they are more likely to eat well, and this can be expected to reduce summer heat exhaustion and stabilize milk quantity and quality.

## Combi Baler Wrapper (MW1011H, MW1231)

### Consistent Work From Bale Shaping To Wrapping



MW1231

The shredding type combi wrap is fully automatic and continuous from bale shaping to wrapping. After bale forming, wrapping can be done immediately.

After forming, the bale is not in direct touch with the ground, so it can be wrapped immediately in a fresher condition for better quality silage.

### Remote Controller

A remote controller is standard equipment.



### Convenient Functions (MW1231)

#### Gull Wing Cover

The covers on both sides of a gull-wing system open and close vertically for easy maintenance.



#### Check Windows

Windows are on the side of the hopper and at the net to check the amount of feed remaining inside the hopper and the net running.



### Cleaning Device Option



MW1011-CC For MW1011H  
MW1231-CC For MW1231

Reducing losses due to feed spilling from the machine with the optional cleaning device.