

SELF-PROPELLED MINI ROLL BALER

SE-512/SR-613(DT-DN)

For Harvesting & Packing Hay and Straw

Reasonable Walking Type with Basic Functions SE-512 Bale Size Φ50×63cm



Self Propelled Walking Type

Chain Bar Type

Bale Size Ф50 x 63cm

Binding: Twine



Open the chamber and release the bale forward.



Easy to operate by the simple struction



Refueling device / Gauge wheel is equipped!

Efficient & Continuous Work with Riding Type (Release bales behind) SR-613(DT,DN) Bale Size Φ50×73cm



Self Propelled Riding Type

Chain Bar Type

Bale Size Ф50 x 73cm Binding : SR-613DT = Twine SR-613DN = Net



Possible to collect cut straw smoothly



Levers for running operation is placed around the driver's seat



Cutting device is equipped. It realizes producing high packing pressure bales and helps you loosen up them during unpacking.

■ Specification

Model	Dimension of Machine(mm)			Weight(kg)	Engine	Output	Operational	*1 Bale Size	Bale Weight(kg)	Binding	Work Speed	Work	Remarks
	Length	Width	Height	weigi i(kg)	Engine	(kW{PS})	Width(cm)	Dia.×W. (cm)	(moisture:20~ 50%)	Material	(km/h)	Efficiency (Min/10a)	Remarks
SE-512	2,050	1,240	1,138	386	Gasoline	M:Rated 3.4{4.7}	70	Ф50×63	10~20	Twine (Saisal•PP)	1.4	40~50	Walking Type
SR-613DT	1,920	1,530	1,350	680	Diesel	Y:Max 4.8{6.5}	102	Ф50×73	14~20	Twine (Saisal•PP)	1.0~3.5 (Continuously Variable Transmission)	30~40	Riding Type
SR-613DN				670						Net (Wid:73cm)		23~30	

^{*1} Bale size differs depending on type of crop and moisture. * Specifications and Pictures are subject to be changed for its improvement.

※仕様・写真は、改良のため予告なく変更することがあります。



You can access our website from the QR code. 安全作業

農業機械は取り扱い説明書をよく読み正しい操作を心がけましょう。 農業機械の使用前後には点検・整備を心がけましょう。





製品のご相談は・・・

本社工場/〒518-0441 三重県名張市夏見2828番地 TEL 0595(63)3111(代) FAX. 0595(64)0857 札幌工場/〒007-0882 札幌市東区北丘珠2条3丁目1番20号 TEL 011(781)1111(代) FAX. 011(781)1113 営業 所/札幌・豊富・北見・中標津・帯広・東北・南東北・関東・関西・中国・九州・南九州 URL: http://www.takakita-net.co.jp

2023/05